

INSPECTION REPORT

Fire Safety Assessment according to EN 45545-2 SENSORswitch HWT2 series

Report-No.: CO 88366 T, Report Date: 10.05.2016
Revision: 1.0, Pages: 10

Customer:

CAPTRON Electronic GmbH
Johann-G.-Gutenberg-Str. 7
82140 Olching
Germany

Order Date: 04.01.2016

Project No.: 717510468

Inspector:

Dipl.-Ing. Sven Ehrenberg
Phone: +49 (89) 5791 3309, Fax: -2999
Mail: sven.ehrenberg@tuev-sued.de

Inspection body Rolling Stock:

TÜV SÜD Rail GmbH
Barthstr. 16
D - 80339 Munich

Content	Page
1. General	3
1.1. Standards	3
1.2. Abbreviations	3
2. Equipment under inspection	4
2.1. Description of equipment	4
2.2. Installation Conditions	4
3. Conformity assessment acc. to EN 45545	5
3.1. Classification according to EN 45545-1	5
3.2. Assessment according to EN 45545-2	5
3.2.1. Material requirements	5
3.2.2. Material verification	7
4. Fire risk analysis	8
5. Summary	9
6. Documents	9

Revision history

Revision	Status	Date	Author	Modified clauses	Modifications
1.0	Final	10.05.2016	Sven Ehrenberg	all	Initial

1. General

1.1. Standards

This document deals with the assessment of the CAPTRON Electronic GmbH, SENSORswitch HWT2 series in respect to compliance with the fire safety requirements as laid down in following standards:

No.	Standard	Date	Title
[R01]	EN 45545-1	2013	Railway applications – Fire protection on rail vehicles – Part 1: General
[R02]	EN 45545-2	2013	Railway applications – Fire protection on rail vehicles – Part 2: Requirements for fire behavior of material and components

Table 1: Standards

1.2. Abbreviations

Abbreviation	Definition
HL	Hazard Level
PCB	Printed circuit board
N/A	Not Applicable
min.	Minimum
max.	Maximum

Table 2: Abbreviations


2. Equipment under inspection

2.1. Description of equipment

The SENSORswitch HWT2 series is developed and designed for application in rolling stock. The following components will be tested for fire safety regulations:

- Circuit board HWT2 series
- Holding fixture
- Fixation flange
- Housing

The Holding fixture, Fixation Flange and the housing are made of plastic parts. The interior of the switch are electronic components on circuit board.



Electrical Data:

- Nominal input voltage: 24 VDC
- Power Consumption: 15 mA
- Max. failure power: 0,36 W

2.2. Installation Conditions

The SENSORswitch HWT2 series are intended for use in passenger areas in rolling stock. The devices are accessible for passengers.

3. Conformity assessment acc. to EN 45545

3.1. Classification according to EN 45545-1

The SENSORswitch is to be used in vehicles of all design categories and for operations corresponding to operating classes 1 to 4.

The target protection requirement will be evaluated in a risk-oriented approach in accordance with EN 45545-1, Section 4.2 “Fire resulting from accidental ignition or arson” and Section 4.3 “Fires caused by technical defects”. The section 4.2 examines typical ignition models involving newspaper, matches, cigarettes and gas lighters. Those shall be taken into consideration in any position freely accessible to passengers and staff (ignition models 1 and 2 in accordance with Annex A, EN 45545-1). The section 4.3 examines ignition models comparable to electrical arcing or overheating and the spread of fire by any potentially flammable gases and liquids present (ignition models 3 and 4 in accordance with Annex A, EN 45545-1). According to section 4.4 larger ignition models (model 5 in accordance with Annex A, EN 45545-1) will be evaluated.

3.2. Assessment according to EN 45545-2

3.2.1. Material requirements

Based on the classification acc. to EN 45545-1, the materials/components shall meet the requirements of Hazard Level HL3. The devices are to be regarded as electro-technical equipment covered by the EN 45545-2 standard. Generally, the requirement sets are listed in section 4.4 “Listed products”. The applicable requirements are the following:

No.	Name	Details	Requirement
EL9	Printed circuit boards	Printed circuit boards without any attached technical equipment	R25 EN 60695-2-11 Glow wire temperature 850 °C or R24 ISO 4589-2:OI min. 32%
EL10	Small electrotechnical products	All electrotechnical equipment, including protection against contact and similar	R26 EN 60695-11-10 min. V0

Table 3: Requirement sets

Connecting cables are not part of the assessment.

In addition to requirements of listed products, the grouping rules acc. to clause 4.3. are applicable for components with low combustible mass and/or surfaces:

- No requirements apply to products with a combustible mass of < 10 g not in touching contact with another unclassified product. (EN 45545-2 clause 4.3.1)

No.	Clause	Requirement	Remark
1-1	4.3.2. Grouping rule 1	< 100 g for interior grouped products	No requirements
1-2	Products without requirements	< 400 g for exterior grouped products	No requirements

Table 4: Grouping rule1

No.	Clause	Requirement	Remark
2-1	4.3.3. Grouping rule 2 Products tested acc. to R24	< 500 g for interior grouped products tested acc. to R24	Proof R24 Oxygen index
2-2		< 2000 g for exterior grouped products tested acc. to R24	Proof R24 Oxygen index

Table 5: Grouping rule2

The following general rules apply:

Clause	Requirement	Remark
4.2. a) General	Products which comply with the highest level of reaction to fire performance and therefore need no further testing are - products classified as A1 according to EN 13501-1 - all products described in commission decision 96/603/EC (as amended)	Metallic housing materials
4.2. n)	If listed products are used in an application below the mass and area thresholds given in 4.3, they may be treated as non-listed products.	---
4.7 Products to be approved on functional necessity	If it can be shown that any of the requirements specified above are not technically achievable with functionally suitable products, then existing commercially available products can be used until and unless a suitable product is developed	digital and analogue circuit elements

Table 6: general requirements EN 45545-2

3.2.2. Material verification

All used materials and those weights are listed in tables as described in D1. All other combustible materials can be treated according to grouping rules or have a mass below 10 g and are therefore not required for verification by test.

Pos.	Description	Weight (ca.)	UL 94	UL No.:
1	HWT2-Aufnahmehalter	17 g	HB	E41613
2	HWT2-Becher	4 g	V-2	E41613
3	Elektrode HWT2	0,4 g	HB	---
4	HWT2-Federblatt	0,8 g	---	---
5	Schutzfolie HWT2-SF02	0,2 g	VTM-2	E93687
6	Platine HWT2-5Pol	4,2 g	V-0	---
7	JST-Stecker 3 pol.	0,4 g	V-0	E60389
8	JST-Stecker 2 pol.	0,3 g	V-0	E60389
9	Bestückung	1,5 g	---	---
10	HWT2-Befestigungsflansch	11,5 g	HB	E41613
11	Total Weight	40,3 g		

Table 7: Material HWT2 series

Material according to EL10

According the requirements EL10, 4 materials with a combined weight of 0,7 g have the proof R26 (V-0).

Grouped Materials according to grouping rule 1 without requirements

Listed materials may, according to 4.2n), be considered as non-listed materials, if they are below the threshold value for weight and surface. Those values are defined in chapter 4.3 of EN 45545-2.

The circuit boards have a combined weight of 4,2 g. The other non-attested materials have a combined value of 35,4 g.

That implies a mass of $4,2 \text{ g} + 35,4 \text{ g} < 100 \text{ g}$. This group can be used without requirements.

Materials according to 4.7

- Electronic components on the circuit boards
The compliance with the essential requirements of 4.1 EN 45545-2 is stated in section 4.

For installation of switches in railway vehicles the distance requirements according to grouping rules have to be considered.

The SENSORswitch, HWT2 series with their combustible materials fulfill the material requisitions according to EN 45545-2 for HL 3.

4. Fire risk analysis

A) Ignition and spread of fire starting from device – material and failure analysis

Fire on electronic devices cannot be excluded. Because of the small content of combustible materials and the low electrical power the fire keeps limited inside the housing. The value of power consumption is max. 0,36 W and is limited by an internal fuse or external circuit line breaker. Therefore in the case of a failure an ignition of combustible materials is unlikely and the spreading of fire is limited to a minimum.

B) Brand inclusion of the components through external/neighboring fire - material-technical and design considerations:

The combustible mass and surface are very small. Therefore, and due to the proven properties of fire promoting the spread of fire is severely limited.

5. Summary

The assessments result is that the CAPTRON Electronic GmbH SENSORswitch HWT2 series meets the requirements as laid down in the fire safety standards – considering the installation areas in railway vehicles:

- EN 45545-2 material: hazard levels HL1 to HL3

For regular (intended) operation the required level of personal safety is ensured.

The assessment is based on documents provided by the costumer (see documents table).

This inspection report was written under the specified accreditation.

TÜV SÜD Rail GmbH
Munich, 10.05.2016



Dr. Jürgen Heyn
Lead Inspector Fire safety



Sven Ehrenberg
Senior Inspector Fire safety

6. Documents

ID	Document	Doc./File ID	Author	Rev.	Date
D1	Material table	---	Captron	---	2015-12-16
D2	Datasheet HWT2	---	Captron	---	2004-11

Table 8: Documents